

CICO TILFI-NSA

SINGLE PACK NON-SAGGING CEMENTITIOUS TILE ADHESIVE

CICO TILFI-NSA is a single pack polymer and cementitious system and is used as an excellent tile adhesive by way of mixing with water at the site. It could be used as a thin or thick bed adhesive for fixing ceramic and mosaic wall and floor tiles. Cured material is grey in colour.

USES

Bonding ceramic wall tiles and mosaic tiles in exterior and interior situations such as bathrooms, toilets, shower recesses, laundries and swimming pools. Can be most suitably applied over rendered brick work, brick masonry and concrete surfaces.

FEATURES

- Resistance to complete immersion.
- Excellent adhesion strength on cement plaster / concrete surfaces.
- Tile fixing permanent.
- Increased resistance to salts, oils, sewage, chemicals, chloride and carbonation.
- Chloride free
- Non-toxic, suitable for drinking water contact.
- Most economical and best performance level among all cementitious system.

TECHNICAL DATA

Colour	Mixed material is grey
Mixing Ratio	25% to 30% water by weight to be mixed with the powder.
Yield (mixed)	1700±100 Kg./cum
Coverage	3-4kg/m ² when applied by 6mm notched trowel
Working Time (approx.)	One hour at 27°C
Curing	As the applied material shall be covered by tile, no curing is required; otherwise normal water curing will do.
Light Foot traffic	After 24 hours at 30°C



Product Data Sheet



PACKAGING

20 Kg Bag

HEALTH & SAFETY

Non-toxic and non-inflammable.

SHELF LIFE

12months in unopened sealed bag

STORAGE

Store in dry cool place and away from direct sunlight.

Important Note:

All CICO products are sold in the market after strict Quality Control in line of ISO 9001 and guaranteed against any manufacturing defect. Although the basic formulation of Company's products generally remains unchanged, production refinements arising from continuing research and evaluation program may occasionally result in marginal changes in properties. CICO aspires to ensure that any recommendation, advice, test data, specification, method statement and other information given in this product datasheet is accurate and best of company's knowledge. Since, the company (CICO TECHNOLOGIES LTD) has no control over the selection of its product, applicators, application methodology, how and where it is applied, therefore, the company cannot accept any liability directly or indirectly arising from the use of its product. It is important to any customer, user or specifier satisfies him / herself that the product is suitable for the intended purpose including health, safety and environmental aspect. Unless or otherwise agreed in writing, all products of the company are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. All customers, users, specifiers should ensure that they examine the suitability of the product with company's latest product data sheet.

CICO TECHNOLOGIES LIMITED

Corp. Office: C-120,2nd Floor, Okhla Industrial Area, Phase –I,New Delhi-110 020 Tel. No: 91-11-4050 9400, Fax: 91-11-4050 9413 E-Mail: cicotech@cicogroup.com Web Site: <u>www.cicogroup.com</u>



DELHI I MUMBAI I KOLKATA I CHENNAI

