

ReArm Krack Fill - W

(Formerly known as MYK KRACK FILL (White))

Crack Repair Mortar



TECHNICAL DATA SHEET

Product Description

It is a cement based polymer modified powder material for filling cracks in plastered surfaces. It is ideal to fill 2 to 3 mm wider static cracks, It has strong adhesion and also non-shrink in nature.

Uses

- To fill the static cracks of 2 to 3 mm sizes
- To level the undulation of the un plastered or plastered ceilings and walls
- To provide smooth finish to brick and stone,

Features and Benefits

- Adhesion - Strong adhesion to common building substrates.
- Easy to use
- Good water resistance properties & weathering durability
- Eco- friendly - Does not content solvent.
- Non shrink in nature

Application Methodology

Mixing & Application:

- Remove all loose particles from the surface then moisten the surface before doing the coating application.
- Then apply ReArm Bond SBR by brush application. Mixing ratio of Crack-Fill Powder to water varies with respect to area of application.
- For surface leveling - the ratio is 2 parts of powder to 1 part of water and mix until we get homogeneous consistency.
- For filling deep holes and cracks - reduce the water quantity to get a thicker pasty consistency.
- Start addition of crack filler powder gradually under continuous mixing till a homogeneous lump free mix is obtained after addition of balance quantity of water.
- For smaller mixes wooden or metal spatula can be used and mixed manually.
- The total mixing time shall not be more than 5 minutes.



ReArm Krack Fill - W

(Formerly known as MYK KRACK FILL (White))

Crack Repair Mortar



TECHNICAL DATA SHEET

Consumption

The coverage varies with different application.
For crack filling-1 kg powder with 250 ml water will fill a crack of 4 mm width by 4 mm depth up to 32 linear meter.

Packaging

Available in 0.5, 1 & 12 Kg pack

Storage and Shelf Life

Store in cool dry place
24 months from date of manufacturing.

Health & Safety

Use of hand gloves is necessary while mixing the product. In case of contact with skin or eyes, use plenty of water to wash and obtain medical helps immediately.

Product Categories Available



Legal Note

The information, and, in particular, the recommendations relating to the application and end-use of MYK Arment products, are given in good faith based on MYK Arment current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with MYK Arment's recommendations. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchant ability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. the user of the product must test the product's suitability for the intended application & purpose. MYK Arment reserves the right to change the properties of its products. the proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local product data sheet for the product concerned, copies of which will be supplied on request.

MYK Arment Private Limited
(Formerly Known as MYK Schomburg India Pvt.Ltd)
8-2-703/A, 3rd Floor, Leela Gopal Towers, Road No. 12, Banjara Hills, Hyderabad -500 034
Tel: +91 40 6816 0001 | Email: myk@mykarment.com | www.mykarment.com