

Description

STP No 1 when used as an admixture forms an internal barrier against water penetration. It also increases the plasticity of mortar, reduces water absorption and thereby guards against freeze-thaw damage.

It is available in powdered form without chlorides or in a liquid formula which contains additives for additional densification of the mortar or concrete. **STP No 1** will not increase the air content of mortar or concrete. It complies with IS 2645.

Characteristics

	STP No 1 (L)	STP No 1 (P)
Appearance	Liquid	Powder
Specific Gravity	1.00 – 1.05	0.70 - 0.80

Application

- Used in mass concrete foundation walls, floors that must be water tight. water tanks, terrace slabs
- Used in mortar for setting masonry and blocks.

Advantages

- Reduces moisture absorption as much as 60%
- Reduces vapor transmission through walls and slabs
- Reduces capillary action
- Provides greater workability

Application Methodology

Add STP No. 1 to concrete or mortar in the following proportions:

Liquid	100 to 200 Ml per 50 kg bag of cement
Powder	1 kg per 50 kg bag of cement

Coverage

- Liquid 0.2 to 0.4% by weight of cement
- Powder 2% by weight of cement

Health & Safety

- Product should not come in contact with the skin and eyes, or be swallowed.
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water. Seek medical advice if irritation persists.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- If swallowed seek medical attention immediately. **Do not** induce vomiting.

Packing

Available in 1 kg & 30 kg Powder and 200 ml, 1 L, 5 L, 20 L & 200 L liquid.

Storage

Store in a cool dry place, under shed, away from heat.

Shelf Life

12 months in original unopened sealed condition.



STP's Businesses

Waterproofing & Insulation
Road Surfacing
Pipeline Coating
Repairs & Rehabilitation
GARA (Grouts & Admixtures)
Other Powder Products
Sealant & Additives
Epoxy Flooring
Protective / Anti-Corrosive Coating
Other Products



